



BD Rowa™ EasyLoad

Technical data

Stock input capacity	Rectangular packs	approx. 11 to 18 seconds per pack*
Packs input capacity	Min. pack dimensions (<i>D × W × H</i>)	35 x 15 x 15 mm
	Max. pack dimensions (<i>D × W × H</i>)	250 x 150 x 120 mm
	Weight	5 - 800 g
Noise level	The average sound pressure level $L_{p,m}$ is 50.1 dB (A).	
Barcodes	Recognition and processing of PZN, PZN8, EAN, and 2D barcodes	
Options	Automatic expiry date detection (<i>stamped or printed</i>) (OCR function)	
Available for	BD Rowa™ Smart BD Rowa™ Vmax 130 BD Rowa™ Vmax 160 BD Rowa™ Vmax 210 BD Rowa™ Vmax 320	
Connection	Directly to BD Rowa™ automated storage and retrieval system (<i>on one side or at the back</i>) Connects via the conveyor system to the BD Rowa™ automated storage and retrieval system Option to fill several machines	
Dimensions (<i>L × W × H</i>)	1,760 x 540 x 1,625 mm	
Weight (<i>belts excluded</i>)	Approx. 300 kg	
Electric parameters	230 V, 50/60 Hz	
Power consumption	Normal mode	130 W
	Operational	79 W
	Standby mode	0.5 W
Colors	white (RAL 9016), anthracite (RAL Design 000-25-00)	

* Value varies according to overall configuration, deviations possible. OCR function will affect speed.

Technical data

Buffer belt capacity 240 packs / meter on the buffer belt
Load capacity up to 160 kg

Buffer belt	Total height	0.91 m	
	Width	0.49 m	
	Length	BD Rowa™ Vmax	1.00 / 1.50 / 2.00 / 2.50 / 3.00 / 4.00 / 6.00 / 8.00 m
		BD Rowa™ Smart	1.00 m

Becton Dickinson Rowa Germany GmbH, Rowastraße, 53539 Kelberg, Germany
+49 2692 92 06 0 tel, +49 2692 92 06 1299 fax

bd.com/rowa



BD, the BD Logo and BD Rowa are trademarks of Becton, Dickinson and Company or its affiliates.
All other trademarks are the property of their respective owners. © 2023 BD. All rights reserved. Jul-2023, BD-55920